







Lithium metal and lithium alloy cells or batteries - 2017 IATA DGR





	UN3090 - PI968 			UN3091 - PI969 	UN3091 - PI970 
Description	Lithium Cells / Batteries loose (bulk)			Lithium Cells/Batteries packed with equipment	Lithium Cells / Batteries contained in equipment
Section	PI968 - Section II		PI968 - Section IB	PI969 - Section II	PI970 - Section II
Lithium metal cells / batteries capacity	Per cell or battery ≤ 0.3g	Per cell: > 0.3g but ≤ 1g	Per battery: > 0.3g but ≤ 2g	Per cell: ≤ 1g Per battery: ≤ 2g	Per cell: ≤ 1g Per battery: ≤ 2g
Maximum number of cells / batteries per package and packages/consignment	N/A	8 cells	2 batteries	>2 batteries > 8 cells	Those necessary to power the equipment and 2 spare
Maximum net weight per package	2.5 kg (CAO)	N/A	N/A	2.5 kg (CAO)	5 kg (PAX & CAO)
"Description of content" statement as per IATA DGR	<i>"Lithium metal batteries in compliance with Section II of PI968" and "CAO"</i>		<i>"Dangerous goods as per attached Shipper's Declaration" and "CAO"</i>	<i>"Lithium metal batteries in compliance with Section II of PI969"</i>	No Requirements
Labeling					No Requirements
Accepted in Time Definite International (door to door)	Forbidden		Yes (See "Note 1")	Yes	Yes
Account approval required for Time Definite Int'l	N/A		Yes	Yes	No
Requirements for Air Capacity Sales (airport to airport)	Select " LB " and mention " CAO " in the restricted commodity type		Select " DG " and mention " CAO " in the restricted commodity type	Select " LB " and mention " Section II " in the restricted commodity type	No Requirements

Note 1: Forbidden to, from, within the ASIA Pacific region due to air carriers restrictions.



As of 1 January 2017: a new hazard label comes into effect with a 2-year transitional period during which time either the existing Class 9 Miscellaneous Dangerous Goods hazard label or the new Class 9 Lithium Battery hazard label may be applied to packages containing lithium batteries prepared in accordance with Section I, IA or IB of the lithium battery packing instructions. Also a new mark comes into effect with a 2-year transition period during which time either the lithium battery mark or the lithium battery handling label may be applied to packages containing lithium batteries prepared in accordance with Section IB or Section II of the lithium battery packing instructions. The need for an additional document to accompany the consignments is no longer required.

Section	PI968 - Section IA 	PI969 & PI970 - Section I 
Per Cell: > 1g Per Battery: > 2g	Accepted as Air Capacity Sales (See "Note 2") - CAO: ≤ 35 kg UN specification packaging required Fully regulated dangerous goods - Class 9 – Select " DG " and mention " CAO "	Accepted as Air Capacity Sales (See "Note 2") - PAX: ≤ 5 KG or CAO: ≤ 35 kg UN specification packaging required (only for PI969) Fully regulated dangerous goods - Class 9 – Select " DG " and mention " PAX " or " CAO "

Note 2: Lithium batteries packed according to PI968 Section IA and PI969/ PI970 Section I are not accepted in Time Definite International when transported via road to, from or transiting an ADR member state.

IMPORTANT: RECALLED OR DEFECTED LITHIUM BATTERIES ARE FORBIDDEN FOR AIR TRANSPORT.